

### 801Xxxx/801Vxxx Ultra MONSTER M10/RAC X - M5/RAC V

Bohrung/orifice:		.018mm	.023mm	.028mm	.033mm	.038mm	.043mm	.048mm	.053mm	.058mm	.064mm	.069mm	.074mm	.078mm	.084mm	.089mm	.099mm	.109mm	.114mm	.129mm	.140mm
Bohrung/orifice:		.007"	.009"	.011"	.013"	.015"	.017"	.019"	.021"	.023"	.025"	.027"	.029"	.031"	.033"	.035"	.039"	.043"	.045"	.051"	.055"
l/min:		0,19	0,34	0,45	0,68	0,91	1,17	1,47	1,78	2,15	2,53	2,95	3,44	3,89	4,42	4,99	6,2	7,52	8,24	10,58	12,32
Winkel/ angle	Spritz- breite/wi dth in cm*:																				
20°	10-15	207	209	211	213	215	217	219	221	223	225	227		231		235					
30°	15-20					315	317	319	321	323	325	327	329	331	333	335					
40°	20-25		409	411	413	415	417	419	421	423	425	427	429	431	433	435	439	443	445		
50°	25-30					515	517	519	521	523	525	527	529	531	533	535	539	543	545		
60°	30-35					615	617	619	621	623	625	627	629	631	633	635			645	651	655
70°	35-40								721	723			729			735					
80°	40-45						817	819	821	823		827		831	833	835					

\*bei 30 cm Spritzabstand / 30 cm distance from surface

### 80Xxxx M10-80Vxxx M5

Bohrung:		.043mm	.048mm	.053mm	.058mm	.064mm	.069mm	.079mm	.084mm	.089mm	.099mm	.105mm	.109mm	.114mm
Bohrung:		.017"	.019"	.021"	.023"	.025"	.027"	.031"	.033"	.035"	.039"	.041"	.043"	.045"
l/min:		1,17	1,47	1,78	2,15	2,53	2,95	3,89	4,42	4,99	6,2	6,9	7,52	8,24
Winkel/ angle	Spritz- breite/wi dth in cm*:													
50°	25-30	517	519	521	523	525	527	531	533	535	539	541	543	545

\*bei 30 cm Spritzabstand / 30 cm distance from surface

### 807Xxxx/807Vxxx Low Pressure MONSTER M10/RAC X - M5/RAC V

Bohrung/orifice:		.028mm	.033mm	.038mm	.043mm	.048mm	.053mm	.058mm	.064mm	.069mm	.074mm	.078mm	.084mm	.089mm
Bohrung/orifice:		.011"	.013"	.015"	.017"	.019"	.021"	.023"	.025"	.027"	.029"	.031"	.033"	.035"
l/min:		0,45	0,68	0,91	1,17	1,47	1,78	2,15	2,53	2,95	3,44	3,89	4,42	4,99
Winkel/ angle	Spritz- breite/wi dth in cm*:													
30°	15-20		313	315										
40°	20-25	411	413	415	417	419	421	423	425					
50°	25-30			515	517	519	521	523	525	527				
60°	30-35				617	619	621	623	625	627	629	631		
70°	35-40						721	723		727	729	731		

\*bei 30 cm Spritzabstand / 30 cm distance from surface

802Vxxx FineFinish M5					
	Spritz- breite/wi dth in cm*:	.008	.010	.012	.014
20°	10-15	208	210	212	
30°	15-20	308	310	312	
40°	20-25	408	410	412	414
50°	25-30		510		

803Xxxx SuperFinish LP M10/RAC X							
Winkel /angle	Spritz- breite/ width in cm*:	.006	.008	.010	.012	.014	.016
10°	5-10	106	108	110	112		
20°	10-15	206	208	210	212	214	
30°	15-20		308	310	312	314	
40°	20-25		408	410	412	414	
50°	25-30			510	512	514	516
60°	30-35						616